

Infant Flow[®] SiPAP System

Comprehensive* specifications



Modes
CPAP
CPAP with apnea/LBR
BiPhasic
BiPhasic with apnea/LBR
BiPhasic tr

Alarms
High pressure
Low pressure
High FiO ₂
Low FiO ₂
Low battery
Low breath rate

Monitored parameters	
nCPAP	0 to 11 cmH ₂ O
MAP	0 to 15 cmH ₂ O**
PIP	0 to 15 cmH ₂ O**
PEEP	0 to 15 cmH ₂ O**
%O ₂	21% to 100%

Warranty
The Infant Flow SiPAP System is warranted to be free from defects in material and workmanship and to meet published specifications for one year from date of shipment.


*Comprehensive model not available in the United States
** BiPhasic tr mode, otherwise 0 to 11 cm H₂O


Controls	
nCPAP/Pressure low flow meter	0 to 15 L/min
Pressure high flow meter	0 to 5 L/min
%O ₂	21% to 100%
Inspiratory time	0.1 to 3.0 seconds
Backup rate	1 to 120 bpm
Rate	1 to 120 bpm
Apnea interval (T-apnea)	10 to 30 seconds (in 5 second intervals)
Manual breath	

Power supply
100 to 230 VAC; consumption 50 VA maximum
12 VDC (sealed lead acid battery); 2 hour life with full charge

Dimensions/weight (driver only)	
Dimensions	10.25" x 15" x 9.25" (26 cm x 38 cm x 23.5 cm)
Weight	19.5 lbs (8.8 kg)

Monitor screen	
Dimension	4.4" x 3.3" (11 cm x 8 cm)
Resolution	320 x 240 pixels, 1/4 VGA with auto-dimming backlight

 CareFusion
22745 Savi Ranch Parkway
Yorba Linda, CA 92887
800.231.2466 toll-free
714.283.2228 tel
714.283.8493 fax

 CareFusion Germany 234 GmbH
Leibnizstrasse 7
97204 Hoechberg
Germany
+49 931 4972-0 tel
+49 931 4972-423 fax



CareFusion
Yorba Linda, CA

carefusion.com

